



# TRENDICOTE PTFE Safety Data Sheet

LEAF/HS/TCOTE

Safety Data Sheet according to new Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830.

Date of issue: 19/04/2021

Revision date:19/04/2021

Replaces version 6.3  
dated: 15/02/2018

Version: 7.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
Product name : Trendicote, PTFE Dry Film Spray  
Product code : TRENDICOTE, TRENDICOTE/60, PTFE Dry Film Spray  
Type of product : Blend  
Vaporizer : Aerosol

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Use of the substance/mixture : Lubricant  
For professional use only.

#### 1.2.2. Uses advised against

No additional information available.

### 1.3. Details of the supplier of the safety data sheet

Trend Tool Technology Ltd.  
Unit 6 Odhams Trading Estate  
St. Albans Road  
Watford  
Herts  
United Kingdom  
T 0044 (0) 1923 249911  
F 0044 (0) 1923 236879

[www.trend-uk.com](http://www.trend-uk.com)

Email address of competent person responsible for SDS:

[technical@trend-uk.com](mailto:technical@trend-uk.com)

### 1.4. Emergency telephone number

Emergency number : 0044 (0) 1202 823699 Wessex Chemical Factors  
Only available during office hours 9am to 5pm Monday to Thursday, 9am to 4pm  
Friday UK time.  
: 0044 (0) 7973 629367 Out of hours emergency number.

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1. : H222; H229  
Skin corrosion/irritation, Category 2. : H315  
Serious eye damage/eye irritation, Category 2. : H319  
Specific target organ toxicity - Single exposure, Category 3, : H336  
Narcosis.  
Hazardous to the aquatic environment - Chronic Hazard, : H411  
Category 2.

Full text of H- and EUH-statements: see section 16.

#### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation.  
Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

Date of issue: 19/04/2021

Revision date:19/04/2021

Replaces version 6.3  
dated: 15/02/2018

Version: 7.0



GHS02



GHS07



GHS09

Signal word (CLP)	: Danger
Hazardous ingredients	: propan-2-ol, isopropyl alcohol, isopropanol; Hydrocarbons, C6, isoalkanes, <5% n-hexane.
Hazard statements (CLP)	: H222 - Extremely flammable aerosol. : H229 - Pressurised container: may burst if heated. : H315 - Causes skin irritation. : H319 - Causes serious eye irritation. : H336 - May cause drowsiness or dizziness. : H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. : P103 - Read label before use. : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. : P251 - Do not pierce or burn, even after use. : P261 - Avoid breathing vapours, mist, spray. : P264 - Wash hands thoroughly after handling. : P271 - Use only outdoors or in a well-ventilated area. : P273 - Avoid release into the environment. : P280 - Wear eye protection, protective gloves, face protection. : P302 + P352 - IF ON SKIN: Wash with plenty of soap and water. : P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. : P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  : P312 - Call a POISON CENTER or doctor/physician/if you feel unwell. : P332 + P313 - If skin irritation occurs: Get medical advice/attention. : P337 + P313 - If eye irritation persists: Get medical advice/attention. : P362 + P364 - Take off contaminated clothing and wash it before reuse. : P391 - Collect spillage. : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.  : P405 - Store locked up. : P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. : P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

**2.3. Other hazards**

Other hazards not contributing to the classification : In use, may form flammable/explosive vapour-air mixture.

**SECTION 3: Composition/information on ingredients****3.1. Substances**

Not applicable.

**3.2. Mixture**

Date of issue: 19/04/2021

Revision date: 19/04/2021

 Replaces version 6.3  
 dated: 15/02/2018

Version: 7.0

Name	Product identifier	%	Classification
Hydrocarbons, C6, isoalkanes, <5% n-hexane (UVCB)	CAS-No.: 64742-49-0 EC-No.: 931-254-9 REACH-no: 01-2119484651-34-XXXX	40 - 60	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336  Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Petroleum gases, liquefied, Petroleum gas, [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately -40 °C to 80 °C (-40 °F to 176 °F).] (contains <0.1%, 1,3-butadiene)  (Propellant) (Note K)	CAS-No.: 68476-85-7 EC-No.: 270-704-2 EC Index-No.: 649-202-00-6	20 - 40	Flam. Gas 1, H220 Press. Gas (Comp.), H280
propan-2-ol, isopropyl alcohol, isopropanol substance with national workplace exposure limit(s) (GB)	CAS-No.: 67-63-0  EC-No.: 200-661-7 EC Index-No.: 603-117-00-0  REACH-no: 01-2119457558-25-XXXX	10 - 20	Flam. Liq. 2, H225  Eye Irrit. 2, H319 STOT SE 3, H336

Note K: The classification as a carcinogen or mutagen applies unless it is shown that the substance contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazards classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall apply.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the component is modified in this case.

Full text of H- and EUH-statements: see section 16.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.
First-aid measures after skin contact	: Gently wash with soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do NOT induce vomiting. Give water to drink. Get medical advice/attention.

##### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/injuries after inhalation	: At high concentrations, the vapours can be irritating to the respiratory system. CAUSES NOSE IRRITATION.
Symptoms/injuries after skin contact	: Irritation.
Symptoms/injuries after eye contact	: Eye irritation.

##### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Date of issue: 19/04/2021

Revision date:19/04/2021

Replaces version 6.3  
dated: 15/02/2018

Version: 7.0

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

Suitable extinguishing media : Dry powder. Carbon dioxide. Polymer foam, Alcohol foam.  
Unsuitable extinguishing media : Do not use a heavy water stream.

**5.2. Special hazards arising from the substance or mixture**

Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container. May burst if heated.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

**5.3. Advice for firefighters**

Firefighting instructions : Use water spray or fog for cooling exposed containers. Do not allow run-off from fire fighting to enter drains or water course.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****6.1.1. For non-emergency personnel**

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fumes/mist/vapours/spray. Avoid contact with skin and eyes.

**6.1.2. For emergency responders**

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

**6.2. Environmental precautions**

Avoid release to the environment. Do not discharge into drains or rivers. Notify authorities if liquid enters sewers or public waters.

**6.3. Methods and material for containment and cleaning up**

For containment : Collect spillage.  
Methods for cleaning up : Absorb and/or contain spill with inert material (vermiculite), then place in suitable container. Mechanically recover the products.  
Other information : Dispose of materials or solid residues at an authorized site.

**6.4. Reference to other sections**

For further information refer to section 13.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well ventilated area. Avoid breathing dust/fumes/gas/mist/vapours/ spray. Avoid contact with skin and eyes. Wear personal protective equipment.  
Hygiene measures : Wash contaminated clothing before use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Date of issue: 19/04/2021

Revision date:19/04/2021

Replaces version 6.3  
dated: 15/02/2018

Version: 7.0

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions. : Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F.  
Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Storage area. : Keep away from food, drink and animal feeding stuffs.

## 7.3. Specific end use(s)

No additional information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

##### propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

##### United Kingdom - Occupational Exposure Limits

Local name	Propan-2-ol
WEL TWA (OEL TWA) [1]	999 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	1250 mg/m <sup>3</sup>
WEL STEL (OEL STEL) (ppm)	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

**Petroleum gases, liquefied, Petroleum gas, [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately -40 °C to 80 °C (-40 °F to 176 °F).] (contains <0.1% 1,3-butadiene) (68476-85-7)**

##### United Kingdom - Occupational Exposure Limits

Local name	Liquefied petroleum gas
WEL TWA (OEL TWA) [1]	1750 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	1000 ppm
WEL STEL (OEL STEL)	2180 mg/m <sup>3</sup>
WEL STEL (OEL STEL) (ppm)	1250 ppm
Remark	Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of -1,3-butadiene)).
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

#### 8.1.2 Recommended monitoring procedures

No additional information available.

#### 8.1.3 Air contaminants formed

No additional information available.

#### 8.1.4 DNEL and PNEC

No additional information available.

#### 8.1.5 Control banding

No additional information available.

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protective equipment

##### Personal protective equipment:

Gloves. Protective goggles.

Date of issue: 19/04/2021

Revision date:19/04/2021

 Replaces version 6.3  
dated: 15/02/2018

Version: 7.0

**Personal protective equipment symbol(s):**

**8.2.2.1. Eye and face protection**
**Eye protection:**

Safety glasses.

Eye protection			
Type	Field of application	Characteristics	Standard
Safety goggles	Splash goggles		EN 166

**8.2.2.2 Skin protection**
**Skin and body protection:**

Wear suitable protective clothing. Chemical resistant apron. Boots.

**Hand protection:**

Protective gloves

Hand protection			
Type	Material	Permeation	Thickness (mm)
	Butyl rubber	6 (>480 minutes)	0.5 mm
	<b>Penetration</b>	<b>Standard</b>	
		EN ISO 374	

**Other skin protection**
**Materials for protective clothing:**

EN 13034.

**8.2.2.3. Respiratory protection**
**Respiratory protection:**

In case of insufficient ventilation, wear suitable respiratory equipment.

Respiratory protection			
Device	Filter type	Condition	Standard
Respiratory protection	Type A - High-boiling (>65°C) organic compounds.	Vapour protection	EN 140

**8.2.2.4. Thermal hazards**

No additional information available.

**8.2.3 Environmental exposure controls**

Avoid release to the environment.

**SECTION 9: Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**

Physical state : Liquid  
 Appearance : Aerosol spray can  
 Colour : No data available

Date of issue: 19/04/2021

Revision date: 19/04/2021

Replaces version 6.3  
dated: 15/02/2018

Version: 7.0

Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < 0 °C
Auto-ignition temperature	: > 230 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.7
Solubility	: In water, material is partially soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: Non oxidizing material according to EC criteria.
Explosive limits	: 0.8 - 12 vol %

**9.2. Other information**

VOC content. : 86%

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Extremely flammable aerosol. Pressurised container: May burst if heated.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

No dangerous reactions known under normal conditions of use.

**10.4. Conditions to avoid**

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

**10.5. Incompatible materials**

No additional information available.

**10.6. Hazardous decomposition products**

Carbon monoxide. Carbon dioxide.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

**propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)**

LD50 oral rat	5045 mg/kg
LD50 dermal rabbit	12800 mg/kg

Date of issue: 19/04/2021

Revision date: 19/04/2021

Replaces version 6.3

Version: 7.0

dated: 15/02/2018

LD50, male, female, Inhalation, rat	> 10000 ppm (6 Hours, (OECD 403 method).
-------------------------------------	--

**Petroleum gases, liquefied, Petroleum gas, [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately -40 °C to 80 °C (-40 °F to 176 °F).] (contains <0.1% 1,3-butadiene) (68476-85-7)**

LD50 Inhalation - Rat	20 mg/l/4h
-----------------------	------------

**Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)**

LD50 oral rat	> 5840 mg/kg
LD50 dermal rabbit	> 2920 mg/kg
LC50 Inhalation - Rat	> 25.2 mg/l/4h

Skin corrosion/irritation	: Repeated or prolonged contact may cause skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT - single exposure	: May cause drowsiness or dizziness.

**propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)**

STOT - single exposure	May cause drowsiness or dizziness.
------------------------	------------------------------------

**Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)**

STOT - single exposure	May cause drowsiness or dizziness.
------------------------	------------------------------------

Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

**PTFE Dry Lubricant**

Vaporizer	Aerosol
-----------	---------

**SECTION 12: Ecological information**
**12.1. Toxicity**

Ecology - general	: Toxic to aquatic life with long lasting effects.
Ecology - water	: Physical properties indicate that petroleum gases will rapidly volatilise from the aquatic environment and that acute and chronic effects would not be observed in practice.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

**propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)**

LC50 - Fish [1]	9640 mg/l Fathead Minnow (Pimephales promelas)
EC50 72h - Algae [1]	> 1000 mg/l (Desmodesmus subspicatus)
EC50, daphnia, short-term	9714 mg/l (24 Hours, (OCED 202 method))
EC5, microorganisms, Pseudomonas putida	1050 mg/l (16 Hours)

**Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)**

LC50 - Fish [1]	> 13.4 mg/l Rainbow trout (Oncorhynchus mykiss)
EC50 - Crustacea [1]	3 mg/l
EC50 72h - Algae [1]	29 mg/l

**12.2. Persistence and degradability**

Date of issue: 19/04/2021

Revision date:19/04/2021

Replaces version 6.3  
dated: 15/02/2018

Version: 7.0

**propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)**

Persistence and degradability	Readily biodegradable
-------------------------------	-----------------------

**Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)**

Persistence and degradability	Readily biodegradable
-------------------------------	-----------------------

**12.3. Bioaccumulative potential**

**propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)**

Partition coefficient n-octanol/water (Log Pow)	0.05
---	------

Bioaccumulative potential	No bioaccumulation
---------------------------	--------------------

**12.4. Mobility in soil**

**propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)**

Surface tension	22.7 mN/m
-----------------	-----------

Ecology - soil	Very mobile. Soluble material/quickly disperses in water.
----------------	---

**Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)**

Ecology - soil	Product evaporates when in contact with the air.
----------------	--

**12.5. Results of PBT and vPvB assessment**

**Component**

propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.  
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

**12.6. Other adverse effects**

No additional information available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Dispose used or damaged aerosol cans at permitted disposal sites. Do not pierce or burn, even after use. Do not burn empty packaging. Do not cut using a blowtorch.

**SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / AND.

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN1950	UN1950	UN1950	UN1950	UN1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
<b>Transport document description</b>				
UN1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ ENVIRONMENTALLY	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY	UN 1950 AEROSOLS, 2.1, ENVIRONMENTAL	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY

Date of issue: 19/04/2021

Revision date: 19/04/2021

 Replaces version 6.3  
 dated: 15/02/2018

Version: 7.0

	HAZARDOUS	HAZARDOUS	LY HAZARDOUS	HAZARDOUS
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: Yes	Dangerous for the Environment: Yes Marine Pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available.				

**14.6. Special precautions for user**
**Overland transport**

Classification code (ADR)	: 5F
Special provision (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1L
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading and unloading (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

**Transport by sea**

Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Stowage and segregation (IMDG)	: SG69

**Air transport**

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

**Inland waterway transport**

Classification code (ADN)	: 5F
---------------------------	------

Date of issue: 19/04/2021

Revision date: 19/04/2021

Replaces version 6.3  
dated: 15/02/2018

Version: 7.0

Special provisions (ADN) : 190, 327, 344, 625  
Limited quantities (ADN) : 1L  
Excepted quantities (ADN) : E0  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01, VE04  
Number of blue cones/lights (ADN) : 1

**Rail transport**

Classification code (RID) : 5F  
Special provisions (RID) : 190, 327, 344, 625  
Limited quantities (RID) : 1L  
Excepted quantities (RID) : E0  
Packing instructions : P207, LP200  
Special packing provisions (RID) : PP87, RR6, L2  
Mixed packing provisions (RID) : MP9  
Transport category (RID) : 2  
Special provisions for carriage - Packages (RID) : W14  
Special provisions for carriage - Loading, unloading and handling : CW9, CW12  
Colis express (express parcels) (RID) : CE2  
Hazard identification number (RID) : 23

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable.

**SECTION 15 : Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU-Regulations**

Contains no REACH candidate substance with Annex XVII restrictions.

Contains no substance on the REACH candidate list.

Contains no REACH Annex XIV substances.

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) N0 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants.

Contains no substance subject to Regulation (EU) N0 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosive precursors.

VOC content : 86%

**15.1.2. National regulations**

No additional information available.

**15.2. Chemical safety assessment**

No chemical safety assessment has been carried out.

**SECTION 16: Other information**

User notes : Sections revised 1 to 16  
Data sources : Regulation (EC) No. 1272/2008 Classification. This mixture has been classified using methods as described in Article 9(4) of Regulations (EC) No.1272/2008.  
Other information : Suppliers own data sheet (Wessex Chemical Factors). Issue date: 10/2/2017.  
Revision date: 27/09/2021. Version 1.1.  
Trend SDS reference : LEAF/HS/TCOTE

Date of issue: 19/04/2021

Revision date:19/04/2021

Replaces version 6.3  
dated: 15/02/2018

Version: 7.0

**Full text of H- and EUH-statements:**

Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard, Category 2.
Asp. Tox.1	Aspiration hazard, Category 1.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2.
Flam. Gas. 1A	Flammable gases, Category 1A.
Flam. Liq. 2	Flammable liquids, Category 2.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: may burst if heated.
H280	Contains gas under pressure: may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Press. Gas (Comp)	Gases under pressure : Compressed gas.
Skin Irrit. 2	Skin corrosion/irritation, Category 2.
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis.

Safety Data Sheet (SDS), EU

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*